

XG30-40kW

Three Phase On-Grid Solar Inverter



- 3-4 MPP Trackers, high single circuit tracking accuracy, fast dynamic response
- 160% DC Input Oversizing
- Maximum efficiency of 98.6%. Wide MPPT voltage range: 200V-1000V
- Compatible with high power modules

 Efficient
Higher Revenue

- Smart I-V Curve Diagnosis Function: locate PV string faults accurately and automatically detect faults
- Intelligent Fault Detection: AC side voltage and current waveforms real-time recorded, fast fault location
- Support RS485 (WiFi/GPRS/Ethernet optional): remote monitoring and operation via PC or mobile phones

 Intelligent
Simple O&M

- IP66 Protection degree: support outdoor installation
- DC & AC Type II SPD: prevent lightning damage
- AFCI Function (Optional): when an arc-fault is detected the inverter immediately stops operation

 Reliable
Worry Free

	XG30KTR	XG33KTR	XG36KTR	XG40KTR
Input (DC)				
Max. Input Power	48 kW	52.8 kW	57.6 kW	64 kW
Max. Input Voltage		1100 V		
Start Voltage		250 V		
Rated Input Voltage		600 V		
Full-load MPP Voltage Range		500 V ~ 800 V		
MPPT Voltage Range		200 V ~ 1000 V		
Number of MPP Trackers	3		4	
String per MPPT		2		
Max. Current per MPPT		26 A		
Max. Short Circuit Current per MPPT		32 A		
Output (AC)				
Max. Output Current	48.3 A	53 A	57.8 A	64.3 A
Rated Output Power	30 kW	33 kW	36 kW	40 kW
Max. Output Power	33.3 kVA	36.6 kVA	39.6 kVA	44 kVA
Rated Grid Frequency		50 Hz / 60 Hz		
Rated Grid Voltage		230Vac / 400Vac, 3L / N / PE		
Power Factor		>0.99 (0.8 leading~0.8 lagging)		
THDi		<3% (Rated Power)		
Efficiency				
Max. Efficiency		98.60%		
European Efficiency		98.50%		
MPPT Efficiency		99.90%		
Protection				
DC reverse polarity protection		Yes		
Anti-islanding protection		Yes		
AC short circuit protection		Yes		
Residual current monitoring unit		Yes		
Insulation resistance monitoring		Yes		
Ground fault monitoring		Yes		
Grid monitoring		Yes		
PV string monitoring		Yes		
Surge protection		Type II		
AFCI protection		Optional		
Communication				
Display		LED / LCD / WiFi/App		
Communication		Standard: RS485 Optional: WiFi / GPRS / Ethernet		
Standard Compliance				
Grid Connection Standards		IEC 61727, IEC 62116, IEC 60068, IEC 61683, VDE-AR-N 4110:2018, VDE-AR-N 4105:2018, VDE-AR-N 4120:2018, EN 50549, AS/NZS 4777.2:2020, CEI 0-21, VDE 0126-1-1/A1 VFR 2014, UTE C15-712-1:2013, DEWA DRRG, NRS 097-2-1, MEA/PEA, C10/11, G98/G99		
Safety / EMC		IEC 62109-1:2010, IEC 62109-2:2011, EN 61000-6-2:2005, EN 61000-6-3:2007/A1:2011		
General Data				
Dimensions (W x H x D)		600 x 430 x 230 mm		
Weight	30 kg		32 kg	
Operating Temperature Range		-30° C ~ +60° C		
Cooling Method		Smart Cooling		
Protection Degree		IP66		
Max. Operating Altitude		4000 m		
Relative Humidity		0 ~ 100%		
Topology		Transformerless		
Night Power Consumption		< 1 W		